



Installation Instructions

Complete set active Sound incl. Soundbooster

VW Tiguan 5N

v1.2 (29.05.2017)

Contents

1	Liability Exclusion	3
2	Copy Right	4
3	General Notes	4
4	Safety instructions	5
5	Requirements for the determinable operation	5
6	Note	5
7	How to connect a cable to another	6
8	Note Cable Inscription/Color	7
9	Assembly Instructions	8
10	Removing trim panels front	9
11	Removing front sill trim and trunk sill covering	10
12	Connection power supply and CAN-Bus	11
13	Connection ground and cable routing in the trunk	12
14	Installation soundbooster and pushbutton	13
15	Important Information Sound Booster	14

1 Liability Exclusion

Dear Customer

Our cable sets are developed according to the connection- and circuit diagrams of the corresponding car manufacturer. Before the original production the cable sets will be tested on an original car. Therefore, the integration into the car electronics will be executed according to the instructions of the manufacturer. Regarding the necessary pre-understanding and the accuracy of the presentation of texts and pictures our mounting guidelines correspond to the usual ones in car technology and car electronics. Practically, they have been proved one's worth a hundred times.

However, should there be any difficulties during the installation of our products we will be at your disposal any time for support by phone or by mail. Moreover, we offer you to execute the installation at our works in Bad Segeberg.

Costs which may arise because a third person will execute the installation of our products will not be supported by us in any case. Only if there is a mistake caused by our product we will pay the proved costs of the installation as well as the costs of the removal of the defective product. The refund of expenses will be limited to gross EUR 110,- ; we reserve the right to check the described mistake in our works in Bad Segeberg. In case of a proved reclamation the costs for dispatch for the check in our factory will be transferred to you.

According to our experience each specific factory which has the necessary diagnostic device, diagnostic software and the circuit diagrams of the manufacturer can find possible mistakes at our products within a short time. So the installation and removal including diagnostic inspection can be realised in at most 60 minutes.

We also made the experience that many specific factories cannot work with the circuit diagrams of the manufacturer, and that they cannot read usual wiring diagrams. Therefore, very easy installation works will take many hours. You will understand that we neither take the risk to find a reliable specific factory nor the financing of the training of the staff of your favoured factory.

Costs which will arise because you buy missing parts or spare parts at other suppliers will be refunded by us up to the amount of the costs which had been arisen by additional supply (saved expenses). In this case, there would be no right for refund according to the legal guarantee right as long as we have no deadline for supplementary performance or a deadline for supplementary performance has not expired.

So if you have any problems with the installation or operation of one of our products please call us, send us an email, send us the product or take your car to our factory in Bad Segeberg. We are sure to find an appropriate solution for each concern.

With best regards

Your Kufatec GmbH & Co. KG Team

2 Copy Right

Our installation- and removal instructions, installation plans, software and other documentation with texts or pictures are protected by copy right.

A publication or distribution of these documents is only permitted with a written approval of Kufatec GmbH & Co. KG.

3 General Notes

Regarding the development there has especially been paid attention to your personal safety together with the most possible operating comfort, modern design and actual product technologies.

Despite most possible accuracy in case of incorrect installation or use or in case of incorrect operating, it is possible that injuries or damages of property may arise.

Therefore, please read the operating instructions you have received carefully and completely, and keep it with you.

All articles of our production will be checked at 100% — for your safety.

We reserve the right to make technical changes which serve the progress at any time.

Before the installation or startup it may be necessary, depending on the article and purpose of use, to check the legal instructions of each country.

In case of warranty claim the device has to be sent to the seller originally packed together with the sales receipt and a detailed description of the mistake. Please consider the manufacturer's instructions for return (RMA). The legal warranty instructions are valid.

The warranty claim and also the permission for startup will expire in case of:

- unauthorised changes on the device or the accessories which have not been executed or approved by the manufacturer or its partners
- opening of the box
- repair of the device on your own
- incorrect use / no normal use / startup
- influence of force on the device (falling down, wilful damage, accident, etc.)

During the installation please consider all safety and legal instructions. The device may only be installed by trained qualified personnel or persons who are similar qualified.

In case of installation- or function problems please reduce the search of the mistake to approx. 0,5 hours for mechanical works or 1,0 hours for electronic works.

To avoid unnecessary additional work and expenses, please send immediately an inquiry to our technical support with the Kufatec contact form (<http://www.kufatec.de/shop/de/infocenter/>)

Please absolutely mention the following:

- car chassis number
- part number of the add-on kit
- exact description of the problem
- work steps already made

4 Safety instructions

The installation may only be executed by trained qualified personnel. Please execute the installations only in a condition of dead voltage. Here please separate for example the battery from the main power supply and consider the instructions of the car manufacturer.

- In order to not endanger your own driving safety please never use security relevant screws, bolts or other fixation pieces at steering, brake system or other components.
- Connect the device only at 12V wiring system voltage with ground connection to the autobody. This assembly is not allowed for the use in trucks or other cars with 24V wiring system voltage.
- Please avoid the installation of the device at positions where the driving safety or the functional efficiency of other subassembly integrated in the car are restricted.
- This module may only be used together with the following mentioned car types and models; the installation may be executed exclusively by use of the circuit points mentioned in the assembly instructions.
- Kufatec GmbH & Co. KG does not assume liability for damages which are caused by incorrect installation, the use of inapplicable circuit points or the installation into car types and -modules which are not foreseen.
- We would like to draw your attention to the fact that the module processes the data of the MOST-protocol of the car mentioned below. Therefore, during the installation of the module it will be used a model-specific complete system which we as the manufacturer of the mentioned construction line only know partly.
- Especially in case of changes within the same model line and the same year we therefore cannot guarantee the applicability of our construction line in each case. Kufatec GmbH & Co. KG does not assume liability for the applicability of our construction line with changes made by the manufacturer.
- Kufatec GmbH & Co. KG does not assume liability that the installation of the here described component has been permitted according to the guarantee instructions of particular car manufacturers. Therefore, please consider the guidelines for installation and guarantee conditions of your car manufacturer before installation.
- The manufacturer reserves the right to change components without giving reasons.
- Subject to errors and changes

5 Requirements for the determinable operation

Please use the device only in its the corresponding area.

In case of unprofessional and untypical use, installation or modification the permission for operation and the warranty claim will expire.

6 Note

Make sure that there's enough space at the described position. If there is no space please cancel the installation and contact our technical support.

The use of a sound booster is not permitted without registration in the vehicle papers, in the area of the german StVZO. The noise emission of the vehicle is increased by this retrofit. The regulations of the StVZO must be observed. It is therefore recommended to ask for a specific registration option at the responsible TÜV/DEKRA office before retrofitting. Outside Germany, please observe the laws on vehicle licensing applicable in your country.

7 How to connect a cable to another




Figure 1: How to connect a cable to another

Table 1: How to connect a cable to another

No.	Work step	Note
1	Take the cable of the vehicle, to which you want to connect, (green marked here) and strip the insulation at one point with a suitable tool (cable stripper/cutter knife).	
2	Now take the cable of the cable set, which you want to connect, (yellow marked here) and strip the insulation at the end.	
3	Twirl the wires of the stripped cable together.	
4	Place the end of the cable you want to connect under the stripped point of the cable of the vehicle...	
5	... and wrap the cable you want to connect around the cable of the vehicle.	
6	Lastly, stick insulating tape around the connection point.	

8 Note Cable Inscription/Color



Figure 2: Cable Inscription

If our cable set consists exclusively of grey wires, connect the wires according to the cable inscription.

9 Assembly Instructions

The following illustration shows the cable routing as well as the position of the individual components.




Figure 3: Vehicle overview

- 1 External sound generator incl. mounting plate
- 2 Control unit for engine sound generation
- 3 Sound Booster Pro (module)

10 Removing trim panels front




Figure 4: Removing trim panels front

Table 2: Removing trim panels front - instructions

Nr.	Work step	Note
1	Remove the left covering of the instrument panel of the dashboard with a trim tool.	
2	The oddments tray is located to the left of the steering wheel. Open it and push the marked guidings inwards to be able to take the tray downward out.	
3	Loosen the upper trim panel of the b-pillar with a trim tool. Pull it slightly forward, but don't remove it completely.	
4	The picture shows the lower trim panel of the b-pillar on the driver's side from the point of view of the back seats. With a trim tool, lever this trim panel out at the marked position in the direction of the interior.	
5	Move the plug of the pushbutton for interior surveillance (if installed) off.	
6	Pull the hood release and, with a flat-blade screwdriver, remove the interlock clip which is located on the back of the lever. Afterwards the lever can be moved off in the direction of the driver's footwell.	

11 Removing front sill trim and trunk sill covering




Figure 5: Removing front sill trim and trunk sill covering

Table 3: Removing front sill trim and trunk sill covering - instructions

Nr.	Work step	Note
1	Loosen the marked screw/clip with a flat-blade screwdriver.	
2	Lever the sill trim up out with a trim tool at the marked position.	
3	Remove the upper trim panel of the c-pillar on the driver's side with a trim tool.	
4	Open the left oddments tray in the trunk and take the things out that are inside.	
5	Take the trunk floor out of the trunk.	
6	The picture shows the trunk sill covering from the point of view of the back seats. Remove the marked clips on the left and on the right.	
6.1	Pull the trunk sill covering slightly forward at the marked points. Afterwards you can pull it up out.	

12 Connection power supply and CAN-Bus




Figure 6: Connection power supply and CAN-Bus

Table 4: Connection power supply and CAN-Bus - instructions

Nr.	Work step	Note
1	Loosen the marked screws of the left trim panel of the trunk. Move it slightly forward off afterwards.	T25
2	Loosen the marked screws of the fuse carrier on the left below the steering wheel and the screw of the air discharge installation of the driver's footwell.	T20
3	Unlock the retral covering of the fuse carrier and move it off afterwards.	
4	With a multimeter, search a free fuse spot which carries ignition lead (we used SB 26). Place the cable for ignition lead (red/white) in. Protect the spot with 7.5A.	
5	Over the removed air discharge installation on the right side in the driver's footwell, behind the lower trim of the instrument panel, the Can-gateway (red plug) is located. Move the marked plug off and remove the plug housing.	
6	Connect CAN-High and CAN-Low as follows: - CAN-High (black/white) to the cable of pin 16 (orange/black) - CAN-Low (black/yellow) to the cable of pin 6 (orange/brown)	

13 Connection ground and cable routing in the trunk




Figure 7: Connection ground and cable routing in the trunk

Table 5: Connection ground and cable routing in the trunk - instructions

Nr.	Work step	Note
1	The picture shows the ground spot at the bottom of the a-pillar in the driver's footwell. Connect the ground cable (brown) there. Afterwards place the control units near the ground spot and pay attention that the cables don't handicap the pedal system and the steering column.	10er socket
2	Route the cable for the soundbooster along the original cable harness to the b-pillar on the driver's side.	
3	Route the cable further from the b-pillar behind the trim panel of the c-pillar up to the back seats.	
4	With a pull through aid, pull the cable behind the left trim panel of the trunk along the arrows to the lower left corner of the trunk.	
5	The picture shows the trunk sill from the point of view of the back seats. Route the cable to the passenger's side of the trunk.	

14 Installation soundbooster and pushbutton




Figure 8: Installation soundbooster and pushbutton

Table 6: Installation soundbooster and pushbutton - instructions

Nr.	Work step	Note
1	Open the right oddments tray in the trunk. Afterwards pull the cable in.	
2	The picture shows the grommet to the underbody in the right oddments tray in the trunk. With a pull through aid, guide the cable for the soundbooster through the grommet to the underbody, until you come out at point 2.1.	
3	The markings show the points on the back right side at the underbody, at which the soundbooster is installed.	
4	Now install the soundbooster. For the right fixation, a suitable screw with nut is required in addition. For the left fixation, the bracket of the exhaust is used.	13er socket
4.1	Secure the soundbooster with the safety rope at a suitable place at the car body.	
5	The picture shows the fuse box on the left behind the oddments tray in the lower trim of the instrument panel. Install the pushbutton for the soundbooster at the marked position.	10er socket

15 Important Information Sound Booster

Please use for the fixation of the Sound Booster suitable high tensile screws. In order to avoid loosening of the screws by vibration please make the screws safe with appropriate factory material e.g. Threadlock. Please additionally check the stability of the Sound Booster regularly and if necessary retighten the screws. In case of no consideration we do not assume liability for possible damages. After successful installation we recommend to cover the sound generator with a zinc spray. Make sure that you cover the opening of the sound generator so that no zinc spray can't get inside the sound generator.

As additional safety the delivered steel cable and the retaining clips have to be tightened on the Sound Booster as well as at a suitable position in the car. This safety cable is an additional security should the tightening screws should be released by vibration.

List of Figures

1	How to connect a cable to another	6
2	Cable Inscription	7
3	Vehicle overview	8
4	Removing trim panels front	9
5	Removing front sill trim and trunk sill covering	10
6	Connection power supply and CAN-Bus	11
7	Connection ground and cable routing in the trunk	12
8	Installation soundbooster and pushbutton	13

List of Tables

1	How to connect a cable to another	6
2	Removing trim panels front - instructions	9
3	Removing front sill trim and trunk sill covering - instructions	10
4	Connection power supply and CAN-Bus - instructions	11
5	Connection ground and cable routing in the trunk - instructions	12
6	Installation soundbooster and pushbutton - instructions	13