



...connecting to the aftermarket

Connects2 Vision

User Manual

CAM-TY5-RT

OEM Reverse Camera Retention Interface
For Toyota Vehicles

APPLICATION:

Toyota

Avalon	2014>
Avensis	2014>
Camry	2014>
Corolla	2014>
Highlander	2014>
Hilux	2014>
Land Cruiser	2014>
Prius +	2014>
RAV4	2014>
Sequoia	2014>
Sienna	2014>
Tacoma	2014>
Verso	2014>
Yaris	2014>
4Runner	2014>

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- OEM Camera Retention Interface
- Instructions

INSTALLATION

1. Connect the yellow RCA connector from the interface to the camera input on the rear of the aftermarket head unit
2. Connect the white connector (24 Pin Connector) from the interface to the vehicle harness
3. Connect the black flying wire to ground
4. Connect the red flying wire to vehicle's 12V ignition
5. Connect the brown flying wire to vehicle's reverse signal feed



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2